

Revolabs RF Armor™ Wireless Microphone Product Specifications

Impervious to Radio Frequency (RF) interference! The RF-Armor version has exceptionally robust shielding which enables the microphone to operate cleanly even when in direct contact with all wireless electronic devices known to cause unwanted audio interference, such as GSM mobile phones, smart phones, etc.

Size

- TABLETOP: 1.5" (3.8 cm) x 0.8" (2.03 cm) x 3.3" (8.4 cm)
- WEARABLE: 0.9" (2.3 cm) x 0.8" (2.03 cm) x 2.6" (6.6 cm)

Weight

- 0.05 lb (0.02 kg)

Radio Frequency

- 1.92-1.93 GHz (DECT in UPSCS)

Acoustic Pickup Pattern

- Omni-directional- 360 degrees
- Uni-directional— 90 degrees

Range

- 65' - 100' (20—30 m) approximately
- Out-of-range alarm

Rechargeable Battery

- Lithium Polymer
- Up to 8 hours talk time

Audio Bandwidth

- 100-6800 Hz

Encryption

- 128-bit authentication

Environmental Requirements

- 40-100 degrees F (5-40 C)
- 20-85% Humidity



Wearable Includes:

- Lanyard
- Earpiece (2.5 mm mono connector, 26" cable with inline volume control, adjustable earpiece containing a 20 mm high quality 32 ohm speaker)

RF Armor Version Wearable Wireless Microphone
03-EXEMICEUEX-BLK-11

RF Armor Version Omni-directional Tabletop Wireless
Boundary Microphone
05-TBLMICEUEX-OM-11

RF Armor Version Uni-directional Tabletop Wireless
Boundary Microphone
05-TBLMICEUEX-DR-11

